CIRCULAR

BMT 24C

Features:

- To operate the machine, simply treadle on the foot switch, the machine will automatically perform clamping and cutting for convenient operation.
- Concealed saw blade performs upward cutting. single or multiple workpieces can be cut simultaneously.
- While cutting, the oil mist splashes automatically for cooling and lubrication.
- Cutting feed is driven by an air/hydraulic combination cylinder for extremely stable cutting speed.
- The machine permits 90 and 45 degree cutting.



U	ni	t:	m	m
---	----	----	---	---

Unit: mm		
MODEL	BMT 24C	
CUTTING ANGLE	90° or 45°	
CUTTING CAPACITY(H×W)	190×190, 150×340 , 80×400, 20×450	
SPINDLE SPEED	2000 rpm	
SAWBLADE SIZE	24"×1" bore	
TABLE AREA	660×700	
TABLE HEIGHT FROM FLOOR	830	
MOTOR	$7\frac{1}{2}$ HP(10 HP opt.)	
AIR PRESSURE	4~6 kgs/cm²	
CONVEYOR LENGTH (OPT.)	1~7 M	
MACHINE DIM.(L×W×H)	1310×830×1460	
PACKING DIM.(L×W×H)	1430×950×1660	
N.W./G.W.	480 kgs/580 kgs	

Suitable for cutting various materials

Aluminium, Brass, Heat sink, PVC, Plastic steel, Bakelite, Acrylic plastic, Teflon, Honeycomb board, Wood and other non-ferrous metals.